

## MANIFOLD GAUGE SET

### Digital manifold HS-370



HS-370-A

#### Technical Parameters

**Pressure value:** gauge pressure  
**Pressure unit:** Kpa; MPa; bar; inHg; Psi.  
**Pressure range:** 0Kpa~6000Kpa  
**Accuracy:** ±0.5%(FS)+5dgt  
**Overload Pressure limit:** 10000Kpa (10MPa; 100bar)  
**Temperature unit:** °C/°F  
**Temperature range:** -40°C~150°C (-40°F~302°F)  
**Temperature accuracy:** ±0.5°C+2dgt ±0.9°F+2dgt  
**Vacuum value:** relative vacuum  
**Vacuum unit:** Kpa; MPa; bar; inHg; Psi.  
**Vacuum range:** -101Kpa~0Kpa

**Power Supply:** 4×1.5V **Connector:** 1/4SAE

#### Accessories:

- HS/TS-1500 temperature sensor: 2pcs
- HS/1.5M charging hose: 1set
- HS/Quick coupler: 1set
- 5# battery: 4pcs
- HS/R410A adapter: 2pcs

**Refrigerant(93):** R11 R113 R114 R115 R116 R12 R123 R124 R125 R1270 R13 R134A R14 R141B R142B R143A R152A R170 R21 R218 R22 R227EA R23 R236EA R245CA R245FA R290 R32 R401A R401B R401C R402A R402B R403A R403B R404A R405A R406A R407A R407B R407C R407D R407E R408A R409A R409B R41 R410A R410B R411A R411B R412A R413A R414A R414B R415A R415B R416A R417A R418A R419A R420A R421A R421B R422A R422B R422C R422D R423A R424A R425A R426A R427A R428A R438A R448A R449A R452A R50 R500 R501 R502 R503 R504 R507A R508A R508B R509A R600 R600A R717 R744(Co2) R1234yf

#### Product Characteristics

- High-strength engineering plastics applied for the housing, make it strong and solid.
- Flexible non-slip silicone design, comfortable to hold.
- High-precision data acquisition unit, stable and accurate.
- Backlight design, easy to operate in low light.
- Micro-power electronics, to extend battery life.
- Built-in 93 kinds of refrigerant database, complete parameters.
- Dual-channel real-time temperature measurement, accurate and convenient.
- Multi-mode selection, full-featured.
- Folding hook, easy to storage.
- High-quality aluminum alloy valve manifold, durable.
- Explosion-proof sight glass, safe and reliable.

## TEMPERATURE MEASURING CLAMP

### HS-TS-1500



#### Technical Parameters

**Temperature unit:** °C/°F  
**Temperature range:** -40°C~150°C (-40°F~302°F)  
**Temperature accuracy:** ±0.5°C+2dgt ±0.9°F+2dgt  
**The length of sensor wire:** 1.5m

#### Product Characteristics

- The shell uses high-strength engineering plastics the whole machine is solid.
- High precision sensor, accurate measurement.
- Flexible jaws, convenient and practical.